

Data sheet I STAMA MC 326 TWIN no. 2057

Pos.	Qty.	Description	Price
100	1,00 ST	<p>Completely refurbished vertical machining centre CHIRON MC 326 TWIN no. 2057</p> <p>Year of construction: 2002, weight: 5.600 kg</p>	
200	1,00 ST	According to described below scope of delivery	
300	1,00 ST	<p>Traverse Ranges</p> <p>Spindle distance A: 266 mm</p> <p>X axis 520 mm</p> <p>Y axis 300 mm</p> <p>Z axis 360 mm</p> <p>Feed Thrust:</p> <p>X-Y axis 4000 N</p> <p>Z axis 8000 N</p>	
400	1,00 ST	<p>Traverse Rates - Axes Dynamic</p> <p>Rapid traverse in X- Y- and Z- axes 60 m/min</p> <p>Feed rate X- Y- and Z- axes 1-10000 mm/min</p> <p>Axis dynamics: a max. (m/sec²) X=5.0; Y=8.0; Z=12.0</p>	
500	1,00 ST	<p>Swivel Table</p> <p>Swivel drive pneumatically controlled.</p> <p>Pneumatically pull down in crown gear</p> <p>Clamping area 2 x 700 x 350 mm</p> <p>Distance table-spindle nose min./max. 200/560 mm</p> <p>Number and size of T-slots per clamping area: 2 x 14 H12</p> <p>Number and diameter of location holes per clamping area: 4 x ø16 F7</p> <p>Acceptable table load 2 x 450 kg</p> <p>Indexing time approx. 1,9 sec.</p>	



Data sheet I STAMA MC 326 TWIN no. 2057

Pos.	Qty.	Description	Price
600	1,00 ST	<p>Spindle Units</p> <p>Tool holder HSK A 63 Draw bar pulling force 8000 N Spindle diameter 65 mm Spindle speed: Standard 12.000 rpm Incl. automatic blowing facility for process safety taper cleaning during tool change. retention force 18000 N Special spindle bearing configuration. Electronically balanced spindle. Balancing after fitting to spindle head.</p>	
700	1,00 ST	<p>Performance Data 60 Nm</p> <p>Torque constant up to 3000 rpm: At 100% cont. duty 31 Nm; at 20% cont. duty 60 Nm Driving power over 3000 rpm: At 100% cont. duty 9,5 Kw; at 20% cont. duty 18,5 Kw Chipping in steel (600 N/mm²):</p> <p>Drilling capacity Ø 25 mm (with insert drill) Tapping capacity M 20 Milling capacity in steel 200 cm³/min (face milling cutter Ø 63)</p>	
800	1,00 ST	<p>Tool Magazine</p> <p>Tool places standard 2 x 21 Tool diameter maximum: all places used ø 88 mm with empty adjacent tool place ø 125 mm (at 100 mm length) Tool length max. 250 mm Tool register HSK A63 DIN 69893 Tool weight max. 5 kg Chip-to-chip time approx. 2,4 sec.</p>	
900	1,00 ST	<p>Tool data management</p> <p>Menu guided tool data management. To each tool are assigned direct: 8-digit tool ident. no. For length and radius offsets service life guideline Data input: At inserting station with input panel or menu guided direct at the display of the control or via interface of the tool presetting</p>	



Data sheet I STAMA MC 326 TWIN no. 2057

Pos.	Qty.	Description	Price
1000	1,00 ST	<p>Measuring System X-Y-Z axis, digital pulse coder (Siemens absolut) Absolute measuring value processing resolution 0.001 mm</p>	
1100	1,00 ST	<p>Installation Data Space required for machine approx. 7 m² Weight approx. 5.300 kg Control voltage 24 V DC Valve voltage 24 V DC Customers side requirement: Working voltage 3x400 V ±10%; 50Hz; N/PE. Connected rating machine 40 KVA Fuse before master switch 3 x 80 A Connected cross section 5 x 25 mm² Required air pressure min. 6 bar ISO 8573-1 Klasse 4 Necessary connection inner diameter Ø13mm</p>	
1200	1,00 ST	<p>Guarding Equipment Enclosure of working area</p>	
1300	1,00 ST	<p>Axis movement with open safety door If the safety door is open, axis movement and spindle rotation are just possible during setting mode. Speed of axis max. 2 m/min. Spindle RPM max. 800 1/min. Actuated by press-button and confirmation key.</p>	
1400	1,00 ST	<p>Lamp in Working Area</p>	
1500	1,00 ST	<p>Permanent Lubrication low-Maintenance All linear guides and ball screws are equipped with long-time lubrication systems, 3 years max. 5000 working hours maintenance-free. After 5000 working hours linear guides and ball screws must be lubricated.</p>	
1600	1,00 ST	<p>Air-Conditioning of the Electrical-Cabinet</p>	
1700	1,00 ST	<p>Coolant equipment with swarf Conveyor Ejection height 850 mm on left side of MC. Integrated wedge wire sieve box, changeable, gap width: 350 µm. Tank for 300 l. External coolant supply integrated in spindle head with adjustable nozzles. If mainly cast iron or light metal has to be machined, additional coolant concentration units are necessary.</p>	



Data sheet I STAMA MC 326 TWIN no. 2057

Pos.	Qty.	Description	Price
1800	1,00 ST	Wash gun For manual cleaning of the loading area.	
1900	1,00 ST	Machine Supports without Coolant Tray for levelling and fixing the machine on the ground. Including all mounting elements.	
2000	1,00 ST	Control Siemens 840D (POWER LINE) TFT Colour display 10,4" NCK-RAM 768 KB (ca. 256 KB for free disposal) Universal-interface RS-232C (V24) Max. 24-digit alphanumeric programme names Forming of sub-routines according to DIN or standard Language and parameter max. nesting 7 times 3D-lin. interpolation G1 (max. 4 axes simultaneously) Circular interpolation G2/G3, helical interpolation Polar or Cartesian coordinates measuring system 49 zero point shifts direct by G-function Inclusive of additive zero point shift Turning of coordinates; Mirror; Scaling factor Insertion of chamfer or radius Siemens standard drilling and milling cycles (additional G81 - G86 same as Siemens 840C) Rigid tapping 32-digit alphanumeric tool identification Tool data input by program or direct with input panel at inserting station Tool life monitoring wear or number of parts Cutter radius compensation G41/G42 by calculation of intersection points or transition radius Restart of program Prompt facility Editing and programming during machining Conversational programming according to DIN 66025 including graphical generating of contour up to 3 axis. Diagnostic displ. and operating feed back in clear text Oriented spindle stop Measuring system: digital absolut incremental encoders Screen saver	



Data sheet I STAMA MC 326 TWIN no. 2057

Pos.	Qty.	Description	Price
2100	1,00 ST	<p>Coolant Filtration Paper 200 l/min Paperband filter, installed on coolant tank 600 l, compact design. Filter width 710 mm. Middle filter mesh 50 microns. A good utilisation of the filter paper is guaranteed due to the high level of fluid. Filter performance 200 l/min - emulsion. With feed-back facility in the event of paper shortage. Including 1 roll of filter paper 710 mm width. Paper transport actuated by level switch.</p>	
2200	1,00 ST	<p>Flow Control Internal Coolant The flow switch is in the coolant line of the interior coolant system installed. In case of the needed pressure can be not arrived, the machine will be stopped.</p>	
2300	1,00 ST	<p>Internal Coolant through Spindles 70 bar Internal coolant supply through work spindles for tool adaptors to DIN 69871 (ISO) form AD or B, or for tool adaptors to DIN 69893 (hollow taper shank) form A > 70 bar high-pressure pump for coolant (22 l/min.) > Incl. Vario valve, pressure is programmable in 7 steps by M-functions. (Applicable only in combination with coolant filtration system filter mesh 50 microns).</p>	
2400	2,00 ST	<p>NC Rotary Table Diameter 160 mm Horizontal NC rotary axis, worm pinion drive by transistor-controlled AC motor. Position measurement by digital pulse coder. Ready for connection including CNC axis, intermediate plate to fit rotary table on machine table and hydraulic locking of table. Rotary table with T-slots and centre bore dia. 30 H7. Centre height 160 mm. Permissible tilting torque 1500 Nm Permissible torque 700 Nm at hydraulic locking. Permissible torque during rotary milling 180 Nm. Speed of rotation 62 rpm Resolution 1/1000 degree. Indexing accuracy ± 25 sec.</p>	



Data sheet I STAMA MC 326 TWIN no. 2057

Pos.	Qty.	Description	Price
2500	1,00	<p>ST Counter Support with Hydraulic Locking Support for rotary table dia. 160 mm or dia. 240 mm. Sturdy design for reception of high cutting forces. Hydraulical locking of flange. Cylindrical locating flange for positioning and mounting of manually or hydraulically actuated fixtures in bridge design. Mounted on console for leveling to rotary table.</p>	
2600	1,00	<p>ST Hydraulic Basic Equipment Necessary in case of hydraulically actuated clamping fixtures. Consisting of: > High pressure aggregate system pressure 250 bar. > 1 hydr. block for 1 circuit double action (2 controlled lines). The clamping line is equipped with a manual pressure adjustment 30-200 bar incl. pressure control (unclamping line 250 bar) Lines are installed up to machine table. > Electrical soft- and hardware. > Additional control panel added to main control panel with funct. clamping, control lamp clamping pressure reached and unclamp fixtures.</p>	
2700	1,00	<p>ST Additional Hydr. Circuit Double Action Extension of hydraulic basic equipment by 1 circuit (2 controlled lines). Workmanship is the same as in the basic equipment.</p>	
2800	1,00	<p>ST Distributor Swivel Table 6-fold Distributor for oil supply to clamping fixtures mounted on one or two sides of swivel table. Central space-saving installation in the middle of the swivel table. Supply through middle of swivel table. The oil-distributor is prepared for the additional supply to electrical units on the swivel table.</p>	
2900	1,00	<p>ST Oil-Distributor 2-fold Counter Support Oil-Distributor 2-fold for oil supply to clamping fixtures mounted on tilting bridge. The oil-distributor is flanged on the counter support. Oil supply up to the mounting flange of the tilting bridge.</p>	



Data sheet I STAMA MC 326 TWIN no. 2057

Pos.	Qty.	Description	Price
3000	1,00 ST	Center height 230 instead of 180 + aligning groove Counter bearing and NC-rotary table differently to the standard center height of 230 mm. Counter bearing axial adjustable from installation dimension 400 to 505. Counter Bearing lead to aligning groove.	
3100	1,00 ST	Full Enclosure of Working Area As protection against swarf and fumes the working area of the machine is completely closed. The drive units are placed outside of the capsule. A suction unit is recommended.	
3200	1,00 ST	Preparation for suction unit Preparation of machine for connection to customer's suction unit. 1 connection nozzle Ø 200 for 1 working area Incl. deflector in the working area	
3300	1,00 ST	Signal Lamp 3 Colours mounted on machine guard. red = machine stop yellow = advance warning green = Automatic cycle	
3400	1,00 ST	- Documentation -	
3500	1,00 ST	Documentation acc. to CE of the first delivery into market 1 x safety regulations in a folder in English 1 x complete documentation on a USB as PDF Language of the operating manuals and safety in English	
3600	1,00 ST	Machine colour Standard painting: 3-coloured light grey/basalt grey RAL 7035/7012/4010 with telemagenta stripes	
3700		Main circuit total power supply 400 / 230V ± 10 %, 50 cycles N/PE, neutral conductor, load possible, pressure supply 6 bar, ± 1 bar at all procedures, room temperature max 40°	
3800		Information Export We point out that the CNC-machining centres are subject to controls. For the export from the European Union an export license is necessary.	



Data sheet I STAMA MC 326 TWIN no. 2057

Pos.	Qty.	Description	Price
3900		<p>Information Machine safety</p> <p>The machine is designed and built in accordance with the European machine guideline, according placing the product on the first time onto the market.</p> <p>Other safety features due to special company rules and specifications can be considered. The actual cost will be invoiced.</p>	
4000		<p>Information Coolant lubrication</p> <p>The machine is designed for standard water soluble coolant and fully enclosed at the standard version. The machine must be equipped with fume extraction.</p> <p>The machine contents different plastics, varnish, resin and glue, which are selected carefully for using coolant and cutting oil.</p> <p>The use of aggressive coolant and additive could cause major damages and machine stops.</p> <p>Contact in any case your coolant supplier before machine set-up and installation.</p>	

