

Data sheet I FZ 12 S FX no. 152-56

| Pos. | Qty. | Description | Price |
|------|---------|---|-------|
| 100 | 1,00 ST | <p>Completely refurbished vertical machining centre CHIRON FZ 12 S FX Nr. 152-56</p> <p>Year of construction: 2000, weight: 6.620 kg</p> | |
| 200 | 1,00 ST | According to described below scope of delivery | |
| 300 | 1,00 ST | <p>Column moving machining centre with NC-swivel equipment</p> <p>Suitable for dry-machining with optimized chip drop Guideways with long-term-grease lubrication</p> | |
| 400 | 1,00 ST | <p>Machine enclosure</p> <p>with loading door, electrically interlocked, 2200 mm high above floor, incl. machine lamp service friendly with removable side walls vertical bellows</p> | |
| 500 | 1,00 ST | <p>2 axis rotary table type ZAS 280</p> <p>consisting of: 4th and 5th axis smallest increment 0,001°</p> <p>Swivel axis (B-axis) Face plate Ø 355° Swing angle 90° ± 15° Tilting accuracy ± 30" with via worm drive system incl. hydraulic clamping system max. transmittable torque 1.100 Nm max. torque if the table is clamped 2.200 Nm max spindle rev. 16 rpm NC-Rotary table (A-axis) faceplate Ø 425 mm with thread and pin hole grid M16 x ø 15 H7 x 50 mm incl pneumatic clamping system Tilting accuracy ± 15" with max. transport weight (workpiece weight): 400 kg via worm drive system max. transmittable torque 1.500 Nm max. torque if the table is clamped 3.000 Nm Max spindle rev. 25 rpm</p> <p>Counter bearing incl. pneumatic clamping system without drive max. torque via clamping system 2.000 Nm</p> | |



Data sheet I FZ 12 S FX no. 152-56

| Pos. | Qty. | Description | Price |
|------|---------|--|-------|
| 600 | 1,00 ST | Travel: X-axis 550 mm Y-axis 400 mm Z-axis 425 mm with variable tool changing level | |
| 700 | 1,00 ST | Main Spindle drive with AC-motor 10,0 KW at 100 % 18,0 KW at 25 % Spindle speed range: 20 - 12.000 rpm - max. 140 Nm Drilling capacity in steel Ø 36 mm (with insert drill) Tapping capacity M 27 Milling capacity in steel 250 cm ³ /min | |
| 800 | 1,00 ST | Automatic tool changer, guaranteed against chips Tool places 20 Tool shaft HSK A63 DIN 69893 Tool-Ø max. 65 mm Tool-Ø if adjacent places are free max. 150 mm Tool weight max. 2,5 kg (5,0 kg on 4 places) Tool changing time approx. 0,9 s (depends on CNC) Chip-to-chip-time approx. 2,4 s (depends on CNC) | |
| 900 | 1,00 ST | AC-servo motors for x-, y- and z-axes digital direct drives with direct absolute encoder rapid traverse in all axes 60 m/min with acceleration of 0,5 g | |
| 1000 | 1,00 ST | SIEMENS CNC-control 840D (MMC 103./ NCU 573.2, 6 measuring cycles, 1 canal) incl. 10,4" TFT colour LCD screen / full keyboard OP032S Hard disk, NC-memory 1,5 GB programmes storage capacity Dialog programming, milling simulation reloading block by block from the hard disk for ISO 66025 programming drilling cycles G81-G89 drilling and milling cycles M- and T- functions circular interpolation (360 degrees) re-start into program Subroutines, parameter programming simultaneous programming contour programming with cycle support support through cycles | |



Data sheet I FZ 12 S FX no. 152-56

| Pos. | Qty. | Description | Price |
|------|---------|--|-------|
| | | <p>polar coordinates, tool offsets for geometry, wear tool radius correction for intersection computing crossingradius, 4 zero offsets G54-G57 30 zero shifts programmable with G-functions 3D and helical interpolation screen switch off mirror function scaling function insert of chamfer and radius Universal interface RS 232C (2 x V24) orientated spindlestop drip feed function through V24 interface dimension metric or inch software limitswitch NC-diagnosis machine-diagnosis absolute indirect path measurement systems, rigid tapping</p> | |
| 1100 | 1,00 ST | <p>CHIRON Powersafe Software package for selective shutdown of installed consumers like axis motors, drives, spindles, seal air, airsensing and ancillary equipment in production breaks or during programmable points in time using a shift calendar. Definable point in time at which the machine starts demand-oriented automatically with a variable warmup programm to recovery the production readiness.</p> | |
| 1200 | 1,00 ST | <p>Working hours and piece counter in the screen</p> | |
| 1300 | 1,00 ST | <p>Thermocontrol</p> | |
| 1400 | 1,00 ST | <p>Signal lamp for 3 signals Signal "red" = failure Signal "white" = machine loaded Signal "green" = machine is running</p> | |
| 1500 | 1,00 ST | <p>Automatic loading door of total enclosure opening and closing, actuating to closing via two-hand push buttons</p> | |
| 1600 | 1,00 ST | <p>Fully enclosed working area</p> | |



Data sheet I FZ 12 S FX no. 152-56

| Pos. | Qty. | Description | Price |
|------|---------|---|-------|
| 1700 | 1,00 ST | Coolant equipment with chip conveyor (scratch band) (for cast iron slurry) discharge height 850 mm, tank capacity 500 l, pump capacity 150 l/min at 1,3 bar pump capacity 20 l/min at 20 bar incl. bed flushing system | |
| 1800 | 1,00 ST | 70 bar high pressure pump flow rate 20 l/min at 20 bar - 11 l/min at 70 bar with vario pressure control valve for 8 programmable pressure stages pre-defined pressure steps (20, 30, 40, 50, 55, 60, 65, 70 bar) instead of standard high pressure pump | |
| 1900 | 1,00 ST | Machine preparation for through tool coolant system including, DIN 69893 HSK A63 collet | |
| 2000 | 1,00 ST | Cabinet cooler as a door mounting unit | |
| 2100 | 1,00 ST | Sheet covering for hydraulic – and pneumatic units | |
| 2200 | 1,00 ST | Direct measuring system A-axis via angle encoder system Heidenhain RON 287 Accuracy: $\pm 8''$ | |
| 2300 | 1,00 ST | Direct measuring system B-axis via angle encoder system Heidenhain RON 287 Accuracy: $\pm 8''$ | |
| 2400 | 1,00 ST | Exhaust fan with air cleaner exhaust capacity 1.000 m ³ /h | |
| 2500 | 1,00 ST | Pneumatic- and Hydraulic Connections | |
| 2600 | 1,00 ST | Pneumatic connection 2-fold, integrated in A- and B-axis, on the face plate | |
| 2700 | 1,00 ST | HAWE Hydraulic unit pressure: 210 bar supply capacity: 6 l/min. incl. valves for supply of 1 clamping device and 1 pressure switch for clamping control | |



Data sheet I FZ 12 S FX no. 152-56

| Pos. | Qty. | Description | Price |
|------|---------|--|-------|
| 2800 | 1,00 ST | Hydraulic connection 2-fold, integrated in A- and B-axis, on the face plate | |
| 2900 | 1,00 ST | Pneumatic connection (A + B) for pneumatic clamping device electrically controlled pneumatic connection, for double acting; pressure control; pressure control switch with automatic pressure regulation. (in case of pressure change automatic pressure sensing) | |
| 3000 | 1,00 ST | Hydraulic connection for 210 bar with 2 connecting couplings "A + B" and hydraulic installation up to outside of machine bed, electrical control for clamping ON - OFF via push button at control panel | |
| 3100 | 1,00 ST | Portable handwheel for conventional travel | |
| 3200 | 1,00 ST | Probe for automatic measuring in the machine Renishaw - probe - package MP10 probe with optical contact module HSK-A63 with installed input-/output switch tracing pin 50 mm with ruby ball dia. 6 mm Interface MI12 bracket for infrared-receiver process oriented measuring software for measuring cycles | |
| 3300 | 1,00 ST | Cutting tools The cutting tools have to be balanced according to VDI 2060, class G 2,0 | |
| 3400 | 1,00 ST | - Documentation - | |
| 3500 | 1,00 ST | Documentation acc. to CE of the first delivery into market 1 x safety regulations in a folder in English 1 x complete documentation on a USB as PDF Language of the operating manuals and safety in English | |
| 3600 | 1,00 ST | Machine colour Two-components-structure varnish - 2 colours light grey acc. to NCS S1502-B basalt grey acc. to RAL 7012 | |



Data sheet I FZ 12 S FX no. 152-56

| Pos. | Qty. | Description | Price |
|------|------|---|-------|
| 3700 | | <p>Main circuit</p> <p>total power supply 400 / 230V \pm 10 %, 50 cycles N/PE, neutral conductor, load possible, pressure supply 6 bar, \pm 1 bar at all procedures, room temperature max 40°</p> | |
| 3800 | | <p>Information Export</p> <p>We point out that the CNC-machining centres are subject to controls. For the export from the European Union an export license is necessary.</p> | |
| 3900 | | <p>Information Machine safety</p> <p>The machine is designed and built in accordance with the European machine guideline, according placing the product on the first time onto the market.</p> <p>Other safety features due to special company rules and specifications can be considered. The actual cost will be invoiced.</p> | |
| 4000 | | <p>Information Coolant lubrication</p> <p>The machine is designed for standard water soluble coolant and fully enclosed at the standard version. The machine must be equipped with fume extraction.</p> <p>The machine contents different plastics, varnish, resin and glue, which are selected carefully for using coolant and cutting oil.</p> <p>The use of aggressive coolant and additive could cause major damages and machine stops.</p> <p>Contact in any case your coolant supplier before machine set-up and installation.</p> | |

