

Offer I CHIRON FZ 08 KSM Nr. 415-10

Pos.	Qty.	Description	Price
100	1,00 ST	<p>Partly refurbished vertical machining centre CHIRON FZ 08 KSM no. 415-02</p> <p>Year of construction: 2005, weight: 3.400 kg</p>	
200	1,00 ST	According to described below scope of delivery	
300	1,00 ST	Column moving machining centre with fixed table Guideways with long-term-grease lubrication	
400	1,00 ST	Machine enclosure with full enclosed workspace with loading doors, electrically interlocked, including replaceable safety windows, workspace enclosure with stainless steel covers, 2070 mm high above floor, including machine lamp	
500	1,00 ST	<p>Digital main drive with spindle 7,0 kW at 100 % 9,0 kW at 25 % - 11 Nm watercooled Spindle speed range up to 30.000 rpm Acceleration and deceleration 0 - 30.000 rpm ca. 1,9 sec. each Warranty: 4.000 h</p> <p>drilling capacity in St 60 Ø 12 mm tapping M 8 milling capacity in St 60 30 cm³/min</p>	
600	1,00 ST	<p>Travel:</p> <p>X-axis 450 mm Y-axis 270 mm Z-axis 310 mm</p>	
700	1,00 ST	<p>Automatic tool changer by robust, full encased Pick up Chain magazine, with mechanic drive protection and cone cleaning above blow out air</p> <p>No. of tools 40 Tool shaft HSK-A 40 DIN 69893 Max. tool dia. max. 50 mm Max. tool dia. max. 100 mm if adjacent places are free Tool length max. 160 mm Max. tool weight max. 1,2 kg Tool change time appr. 0,8 s (depends on control) Chip-to-chip-time appr. 2,5 s (depends on control)</p>	



Offer I CHIRON FZ 08 KSM Nr. 415-10

Pos.	Qty.	Description	Price
800	1,00 ST	<p>Fixed table with chip pan for optimal chip drop at wet- and dry milling clamping surface 770 mm x 290 mm with thread and locating hole grids M16 x ø 15 H7 x 50 mm table loading capacity max. 500 kg</p>	
900	1,00 ST	<p>Digital feed drives for X-, Y- and Z-axis with digital direct drives and indirect absolut path measuring system rapid traverse in X- and Y-axes 60 m/min, Z-axis 60 m/min, acceleration: 1,0 g in X-axis 1,5 g in Y-axis 2,0 g in Z-axis Remark: With normal conditions the machine does not have to be anchored to the floor. (For slippery floors we recommend anchoring.)</p>	
1000	1,00 ST	<p>FANUC 18 i - 3-axes continuous path control 9.5" LCD monochrom screen memory capacity 128 KB drilling cycles G81-G89 absolute path measuring system M- and T-functions circular interpolation (360 degrees) re-start into program makro B sub-routines look ahead simultaneous programming automatic corner override 32 tool offsets cutter radius - contour compensation 6 zero shifts G54-G59 metric/inch switch</p> <p>3 D-interpolation/helical interpolation S-analogue rigid tapping orientated spindle stop Slot for PCMCIA memory card Interface RS 232C on the side at the control panel software-limitswitch NC-diagnosis machine diagnosis</p>	



Offer I CHIRON FZ 08 KSM Nr. 415-10

Pos.	Qty.	Description	Price
		DATA-Server 64 MB memory	
		S-Ram-extension: 1 MB (ca. 5165 KB free available)	
1100	1,00 ST	CHIRON Maintenance Management in the screen display of the pending maintenance: - advance warning = "prepare maintenance" - warning = "carry out maintenance" - machine stop = "catch up on maintenance" Abridged instructions for the pending maintenance with graphic illustration on CD-ROM. Password protected confirmation of the performed maintenance through the maintenance staff.	
1200	1,00 ST	Tool lifetime control with: tool place organization, sister tool organization, drill- and milling cycles 6-digital toolnumbers	
1300	1,00 ST	Thermocontrol (deactivated with use of measuring systems e.g. spindle probe, stationary 3D probe or laser control)	
1400	1,00 ST	Thermodrive with indirect path measuring system	
1500	1,00 ST	Installation elements	
1600	1,00 ST	Wash gun	
1700	1,00 ST	Working hours and piece counter in the screen	
1800	1,00 ST	Socket 230 V at control panel	
1900	1,00 ST	Socket for portable mini-hand wheel without emergency stop button, at control panel	
2000	1,00 ST	Cabinet cooler as a door mounting unit	



Offer I CHIRON FZ 08 KSM Nr. 415-10

Pos.	Qty.	Description	Price
2100	1,00 ST	Oil-free air service unit with automatic condensate separator, pressure control of the air supply and microfilter 0,01 µm for air purge	
2200	1,00 ST	Signal lamp on machine enclosure for 3 signals Signal "red" = failure Signal "white" = load machine Signal "green" = machine is running	
2300	1,00 ST	Coolant equipment with chip container tank capacity appr. 100 l pump capacity 60 l/min at 1 bar Coolant cleaning through interchangeable sieve box and sedimentation basin	
2400	1,00 ST	Additional coolant tank tank capacity 500 l, pump capacity 100 l/min at 1,8 bar (only in combination with chip conveyor, the pump in the chip conveyor becomes the lift pump) coolant filtration via paperbondfilter 50 µm with automatic filter transport	
2500	1,00 ST	- Documentation -	
2600	1,00 ST	Documentation acc. to CE of the first delivery into market 1 x safety regulations in a folder in English 1 x complete documentation on a USB as PDF Language of the operating manuals and safety in English	
2700	1,00 ST	Machine colour Two-components-structure varnish - 3 colours window grey acc. to RAL 7040 grey white acc. to RAL 9002 basalt grey acc. to RAL 7012	
2800		Main circuit total power supply 400 / 230V ± 10 %, 50 cycles N/PE, neutral conductor, load possible, pressure supply 6 bar, ± 1 bar at all procedures, room temperature max 40°	
2900		Information Export We point out that the CNC-machining centres are subject to controls. For the export from the European Union an export license is necessary.	



Offer I CHIRON FZ 08 KSM Nr. 415-10

Pos.	Qty.	Description	Price
3000		<p>Information Machine safety</p> <p>The machine is designed and built in accordance with the European machine guideline, according placing the product on the first time onto the market.</p> <p>Other safety features due to special company rules and specifications can be considered. The actual cost will be invoiced.</p>	
3100		<p>Information Coolant lubrication</p> <p>The machine is designed for standard water soluble coolant and fully enclosed at the standard version. The machine must be equipped with fume extraction.</p> <p>The machine contents different plastics, varnish, resin and glue, which are selected carefully for using coolant and cutting oil.</p> <p>The use of aggressive coolant and additive could cause major damages and machine stops.</p> <p>Contact in any case your coolant supplier before machine set-up and installation.</p>	

