

Data sheet I CHIRON FZ 12 KW no. 253-13

Pos.	Qty.	Description	Price
100	1,00 ST	Completely refurbished vertical machining centre CHIRON FZ 12 KW no. 253-13 Year of construction: 2005, weight: 7.500 kg	
200	1,00 ST	According to described below scope of delivery	
300	1,00 ST	Type 12 Processing medium cooling lubricant	
400	1,00 ST	Column moving machining centre with machine bed in mineral cast technique and workpiece swivel table Guideways with long-term-grease lubrication	
500	1,00 ST	Machine enclosure 2140 mm high above floor with sliding doors, electrically interlocked, incl. machine lamp service friendly with removable side walls working area with vertical bellows	
600	1,00 ST	Travel: X-axis 550 mm Y-axis 320 mm Z-axis 360 mm	
700	1,00 ST	Main spindle drive with AC-motor 7,5 kW at 100 % 13,0 kW at 25 % Spindle speed range: 20 - 15.000 min ⁻¹ - 70 Nm Drilling capacity in steel 60 \varnothing 25 mm (with insert drill) Tapping capacity M 20 Milling capacity in steel 60 120 cm ³ /min.	
800	1,00 ST	Workpiece swivel table 0/180 degrees with centre divider made of sheet metal clamping surface 2 x 660 mm x 350 mm with thread and locating hole grid M16 x \varnothing 15 H7 x 50 mm workpiece swivel time appr. 2,0 s weight-dependent, self-regulating through self-learning speed-control table loading capacity per side 300 kg, max. 100 kg weight difference between the two table sides	

Data sheet I CHIRON FZ 12 KW no. 253-13

Pos.	Qty.	Description	Price
900	1,00 ST	Automatic tool changer through robust, full enclosed pick up tool changer, with mechanical impact protection an cleaning of the tool taper through air blow No. of tools 24 Tool taper HSK-A 50 DIN 69893 Max. tool dia. max. 60 mm Tool length max. 250 mm Max. tool weight max. 3 kg Tool change time appr. 0,9 s (depends on CNC) Chip-to-chip-time appr. 2,4 s (depends on CNC)	
1000	1,00 ST	Mini-operating panel with start and receipt push buttons, for pallet recognition M61/M62	
1100	1,00 ST	AC-servo motors for x-, y- and z-axes digital direct drives with indirect absolut path measuring system rapid traverse in all axes 75 m/min. Acceleration: X-axis 1 g, Y-axis 1,5 g, Z-axis 2,0 g Remark: With normal conditions the machine does not have to be anchored to the floor. (For slippery floors we recommend anchoring.)	
1200	1,00 ST	Fanuc 18i MB – 5 axes continuous path control 10,4“ LCD monochrom screen Memory capacity 256 KB Drilling cycles G81-G89 Absolute path measuring system M- and T-functions Circular interpolation (360 degrees) Re-start into program Makro B subroutines Look ahead Simultaneous programming Automatic corner override 32 tool offsets cutter radius – contour compensation 6 zero shifts G54-G59 metric/inch switch 3D-Interpolation/helical interpolation S-analogue Rigid tapping	

Data sheet I CHIRON FZ 12 KW no. 253-13

Pos.	Qty.	Description	Price
		Orientated spindle stop Slot for PCMCIA memory card Interface RS 232C on the side at the control panel Software-limitswitch NC-diagnosis / machine diagnosis	
1300	1,00 ST	Oil-free air service unit with automatic condensate separator, pressure control of the air supply and micro filter 0,01 µm for air purge	
1400	1,00 ST	CHIRON Maintenance Management in the screen Display of the pending maintenance: Advance warning = "prepare maintenance" Warning = "carry out maintenance" machine stop = "catch up on maintenance" Abridged instructions for the pending maintenance with graphic illustration on CD-ROM. Password protected confirmation of the performed Maintenance through maintenance staff.	
1500	1,00 ST	Thermodrive at indirect absolut path measuring system	
1600	1,00 ST	Working hours and piece counter in the screen	
1700	1,00 ST	Socket 230 V at control panel	
1800	1,00 ST	Socket for portable mini-hand wheel without emergency stop button, at control panel	
1900	1,00 ST	Coolant equipment tank capacity 350 l. with low pressure pump 100 l/min. at 2,1 bar, till 200 l/min. at 1,9 bar incl. tub flushing	
2000	1,00 ST	Machine preparation for through tool coolant system including: <ul style="list-style-type: none"> - Sealing system in the DIN 69871 Form A40 or DIN 69893 HSK A63* collet - coolant distributor installed at the main spindle drive - Coolant leakage sensor - Implemented mud flap in the high pressure piping 	

Data sheet I CHIRON FZ 12 KW no. 253-13

Pos.	Qty.	Description	Price
		- Solenoid valve, controlled via machine program	
		* At HSK A63 we recommend for tool holders the use of our patented coolant tube with sieve. Advantages: - Decrease of the clogging in the internal coolant channel. - Reduction of the wear at the O-ring seal in the collet.	
		(Subject: required high pressure equipment)	
2100	1,00 ST	Wash gun with 1 connection and quick coupling each in loading- and working area	
2200	1,00 ST	Installation elements	
2300	1,00 ST	Chip conveyor (scratch band) instead of standard coolant equipment discharge height 490 mm tank capacity 100 l, pump capacity 110 l/min at 1,3 bar coolant cleaning through slot filter box mesh size W=0,35 mm	
2400	1,00 ST	Coolant equipment tank capacity 350 l. with low pressure pump 100 l/min. at 2,1 bar, till 200 l/min. at 1,9 bar incl. tub flushing	
2500	1,00 ST	Signal lamp for 3 signals Signal "red" = failure Signal "white" = machine loaded Signal "green" = machine is running	
2600	1,00 ST	Cabinet cooler as a door mounting unit	
2700	1,00 ST	Electric cabinet – Indoor light Connected in front of the main switch	
2800	1,00 ST	Flow control switch for internal coolant	

Data sheet I CHIRON FZ 12 KW no. 253-13

Pos.	Qty.	Description	Price
2900	1,00 ST	Package m-functions m72/m73 2 m-function pairs for m74/m75 simple ON/OFF function m76 m-functions to control a m78 peripheral equipment with external setback (blocking of the machine course)	
3000	1,00 ST	Electric interface for loader with "Profibus" - Fanuc for automatic loading system, with DP/DP-coupler (Slave) in the cabinet, for shuttle machining, according to documentation of CHIRON loader interface, consisting of: circuit diagram, signal description and functional diagram, Interface tested according to Chiron-description V03.01, incl. key-operated switch and indicator lamp in the control panel "with loader". Deviation from the standard interface and set up will be charged according to effort. Waiting periods during set up will also be charged.	
3100	1,00 ST	Pneumatic- and Hydraulic Connections	
3200	1,00 ST	Hydraulic connection for 200 bar with 2 connecting couplings "A + B" and hydraulic installation up to outside of machine bed, electrical control for clamping ON - OFF via push button at control panel	
3300	1,00 ST	Pneumatic connection for pneumatic clamping device electrically controlled pneumatic connection, for double acting; pressure control; pressure control switch with automatic pressure regulation. (in case of pressure change automatic pressure sensing)	
3400	1,00 ST	Pneumatic shut off valve maker Ross	
3500	1,00 ST	- Documentation -	
3600	1,00 ST	Documentation acc. to CE of the first delivery into market 1 x safety regulations in a folder in English 1 x complete documentation on a USB as PDF Language of the operating manuals and safety in English	

Data sheet I CHIRON FZ 12 KW no. 253-13

Pos.	Qty.	Description	Price
3700	1,00 ST	<p>Machine colour</p> <p>Two-components-structure varnish - 2 colours light grey acc. to NCS S1502-B basalt grey acc. to RAL 7012</p>	
3800		<p>Main circuit</p> <p>total power supply 400 / 230V ± 10 %, 50 cycles N/PE, neutral conductor, load possible, pressure supply 6 bar, ± 1 bar at all procedures, room temperature max 40°</p>	
3900		<p>Information Export</p> <p>We point out that the CNC-machining centres are subject to controls. For the export from the European Union an export license is necessary.</p>	
4000		<p>Information Machine safety</p> <p>The machine is designed and built in accordance with the European machine guideline, according placing the product on the first time onto the market. Other safety features due to special company rules and specifications can be considered. The actual cost will be invoiced.</p>	
4100		<p>Information Coolant lubrication</p> <p>The machine is designed for standard water soluble coolant and fully enclosed at the standard version. The machine must be equipped with fume extraction.</p> <p>The machine contents different plastics, varnish, resin and glue, which are selected carefully for using coolant and cutting oil.</p> <p>The use of aggressive coolant and additive could cause major damages and machine stops.</p> <p>Contact in any case your coolant supplier before machine set-up and installation.</p>	